

CD10177/12/CH ,CD10410/12/PB ,CD10032/12/SBB Assembly and Installation Instructions

WARNINGS AND CAUTIONS FOR ALL BELOW

1. Fully read these instructions before starting installation, keep installation instructions for future references.
2. Installation is to be performed by a licensed electrician in accordance with the National Electrical Code (NEC) and local authoritative regulations.
3. To prevent electrical shock or hazards ensure electricity is powered off at circuit breaker before re-lamping or wiring of the fixture. Do not install without properly powering off designated area for fixture to be installed.

CAUTION: HEAVY FIXTURE, THE JUNCTION BOX NEEDS TO BE REINFORCED BEFORE INSTALLATION, ALL MOUNTING SCREWS MUST SCREW INTO A MINIMUM OF 1" OF WOOD BEHIND THE DRYWALL. DO NOT MOUNT THIS FIXTURE JUST TO DRYWALL. (All wood that you screw into must be secured to cross beams/ceiling joists behind the drywall).
THIS PRODUCT IS DESIGNED TO BE MOUNTED ON A CORRECTLY INSTALLED STANDARD ROUND OR OCTAGON BOX.
TWO PERSON INSTALLATION

ASSEMBLY INSTRUCTIONS - CHANDELIER

1. Remove fixture from its original packaging, verify all components and complete a visual inspection.

- | | |
|-------------------------|--------------------------|
| A. Mounting Plate (1) | B. Mounting Screws (2) |
| C. Wire Connectors (3) | D. Canopy (1) |
| E. Quick Links (2) | F. Thread Ring (1) |
| G. Wire (1) | H. Decorative Chain (1) |
| I. Loop (1) | J. Central Rod (1) |
| K. Long Glass rod (8) | L. Middle Glass rod (16) |
| M. Short Glass rod (16) | N. Threading Rod (1) |
| O. Fixture Body (1) | P. Decorative Cap (12) |
| Q. Metal Round Disc (1) | R. Decorative Finial (1) |
| S. Hex Nut (30) | T. Big Hex Nut (1) |
| U. Steel Cable Nut (1) | |

2. Pre-plan, make sure all Warnings and Cautions above have been completed.
 - Decide on the hanging height of fixture top to bottom, prepare (H) decorative chains to lengths by removing links not required.

3. Have the wire (G) pass through threading rod (N), central rod (J) and loop (I) and fix the central rod onto the joint of the fixture body (O).

4. Remove the decorative finial (R) and the big hex nut (T), remove the metal round disc (Q) from the fixture body (O), let the glass rods pass through metal round disc (Q) and lock with hex nut (S) and decorative cap (P).

5. Let the glass rod frame pass through the fixture body (O) and lock with big hex nut (T) and decorative finial (R).

6. Have the wire (G) pass through decorative chain (H), thread ring (F), canopy (D), mounting plate (A) and quick link (E) and fix the loop (I) on top of central rod (J), connect the quick link (E) of chain to the loop mounting plate (A).

7. Install mounting plate (A) to junction box with (B) mounting screws.

8. You are now ready to install the fixture to the ceiling. You will require minimum two people to complete the install.

- First connect the safety cable to a secure strong supporting area. See Illustration below on Page 1.
- Connect all the wires and ground using (C) wire connectors by twisting matching wires as below.
 - Ground Wire (G, Green or Copper Wire) Green to Green or Copper to Green or Copper to Copper from junction box.
 - Live Wire (L, Black) Black to Black Wire from junction box.
 - Neutral Wire (N, White) White to White Wire from junction box.
 Once all connected, proceed to next step.

9. Raise the (D) canopy cover to the affixed mounting plate (A) until loop pass through canopy and secure with (F) thread ring.

10. You are now complete and can install bulb (not included) by rotating.
(Installation Map on Page 1)

