

SF50010/3/AGB, SF50011/3/SBB Assembly and Installation Instructions

WARNINGS AND CAUTIONS FOR ALL BELOW

1. Fully read these instructions before starting installation, keep installation instructions for future references.
2. Installation is to be performed by a licensed electrician in accordance with the National Electrical Code (NEC) and local authoritative regulations.
3. To prevent electrical shock or hazards ensure electricity is powered off at circuit breaker before re-lamping or wiring of the fixture. Do not install without properly powering off designated area for fixture to be installed.

CAUTION: HEAVY FIXTURE, THE JUNCTION BOX NEEDS TO BE REINFORCED BEFORE INSTALLATION, ALL MOUNTING SCREWS MUST SCREW INTO A MINIMUM OF 1" OF WOOD BEHIND THE DRYWALL. DO NOT MOUNT THIS FIXTURE JUST TO DRYWALL. (All wood that you screw into must be secured to cross beams/ceiling joists behind the drywall). THIS PRODUCT IS DESIGNED TO BE MOUNTED ON A CORRECTLY INSTALLED STANDARD ROUND OR OCTAGON BOX. TWO PERSON INSTALLATION

ASSEMBLY INSTRUCTIONS - FLUSH MOUNT

1. Remove fixture from its original packaging, verify all components and complete a visual inspection.

- A. Plastic Anchors (4)
- B. Mounting Plate (1)
- C. Anchors Screws (4)
- D. Wire Connectors (3)
- E. Mounting Screws (2)
- F. Canopy Cover (1)
- G. Decorative Canopy Nuts (4)
- H. Fixture Body (1)
- I. Steel Cable Nut (1)

2. Pre-plan, make sure all Warnings and Cautions above have been completed.

3. Fix plastic anchors (A) into ceiling accordingly. Lock the fixture (E) mounting screws onto mounting plate.

4. Secure mounting plate (B) tight onto junction box and ceiling with (E) mounting screws and anchors screws (C).

5. Now you can install the bulbs.

6. You are now ready to install the (H) fixture body to the ceiling.
 - Connect the safety cable to a secure strong supporting area. See Illustration below on Page 1.

- Connect all the wires and ground using (D) wire connectors by twisting matching wires as below.

- Ground Wire (G, Green or Copper Wire)

Green to Green or Copper to Green or Copper to Copper from junction box.

- Live Wire (L, Black) Black to Black Wire from junction box.

- Neutral Wire (N, White) White to White Wire from junction box.

- Once all connected, proceed to next step.

7. Raise the (F) canopy cover to the affixed mounting plate (B) until screw are through canopy and is flush to ceiling. Secure with (G) decorative canopy nuts.

8. You are now complete and can install light bulbs (Installation Map on Page 1)

