


ZEDV

L I G H T I N G

ASSEMBLY AND INSTALLATION INSTRUCTIONS


**ITEM NO.: CD10313-22/P-AGB
CD10313/22/AGB
CD10384/22/PN**



NOTE: Before starting installation of this Fixture or the removal of a previous Fixture, disconnect the power by turning off the circuit breaker or removing the fuse from the fuse box.


STEP1:

Assemble the Rods(B、C、D) onto fixture body(A).
get the desired fixture height.




STEP 2:

Secure mounting plate(G) tight against on ceiling
by 4pcs metal anchors(E) and 4pcs nuts(H), and
use 2pcs screws(I) to secure the mounting
plate(G) on the junction box(F not include).



STEP 3.:

Use the quick link(K) to hang top of two group rods onto
the ring(J) of canopy and tighten the nuts on the quick
link(K).





NOTE: Before starting installation of this Fixture or the removal of a previous Fixture, disconnect the power by turning off the circuit breaker or removing the fuse from the fuse box.

STEP 4:

Wrap the Ground wire from the fixture around the screw on the mounting plate.


Connect the Ribbed Silver Wire from the fixture to the white wire (Neutral wire) from Junction box with wire connector(L)

Connect the Smooth Silver Wire from the fixture to the black wire (Live wire) from junction box with wire connector(L)




STEP 5.:

Align the Canopy (M) with the mounting plate(G), the mounting screws from mounting plate pass through the Canopy holes secured tight with 2pcs cap finials(N) on the mounting screws.



STEP 6.:

Insert 22pcs G9 bulbs(O not include) into the socket first, Then insert the Glass bars (by turns of: B → A up →A down →C →B) onto the fixture body(A), See right picture.




STEP 7:

Connect breaker and turn on Light.

Cleaning & Care:

To clean, wipe the Fixture with a soft, dry cloth. Avoid the use of harsh or abrasive chemicals as they may damage the finish.

SAFETY CABLE ASSEMBLY



1. Remove Hex Nut from Cable Lock Nut and pull Cable Lock Nut from Safety Cable.

2. Join Fixture Safety Cable with safety cable from ceiling and wrap both safety cables around the Cable Lock Nut.

3. Secure by tightening both Hex Nuts until tight.