

CD10314/32/AGB CD10382/32/PN

Assembly and Installation Instructions

WARNINGS AND CAUTIONS FOR ALL BELOW

1. Fully read these instructions before starting installation, keep installation instructions for future references.
2. Installation is to be performed by a licensed electrician in accordance with the National Electrical Code (NEC) and local authoritative regulations.
3. To prevent electrical shock or hazards ensure electricity is powered off at circuit breaker before re-lamping or wiring of the fixture. Do not install without properly powering off designated area for fixture to be installed.
4. This product is designed to be mounted on a correctly installed standard round or octagon junction box.
5. May require 2 people for installation.

ASSEMBLY INSTRUCTIONS - PENDANT

1. Remove fixture from its original packaging, verify all components and complete a visual inspection.

- A. Wire nuts (3)
- B. Metal concrete screws (2)
- C. Mounting plate (1)
- D. Mounting plate screws (2)
- E. Canopy (1)
- F. Decorative nuts (2)
- G. Safety secure rings (2)
- H. 3"suspension stem+hanging ring (2)
- I. 6"suspension stem (2)
- J. 12"suspension stem (6)
- K. Light frame (1)
- L. Glass rod (1)

2. Pre-plan, make sure all Warnings and Cautions above have been completed.

3. Connect the 3"suspension stem(H)、6"suspension stem(I)、12"suspension stem(J) in order; pass the power wire through connected stem and canopy(E), then screw one end of stem to light frame(K), and the other end to the hanging ring of canopy(E) with safety secure ring(G).

4. Lock the mounting plate(C) to junction box and make a remark, fix the metal concrete screw to the ceiling with metal concrete screw(B).

5. Uplift the light fixture (at least two people are required), fix the mounting plate(C) with mounting plate screw and hex nut, fix the steel cable with safety secure ring(M).

6. You are now ready to mount the back plate to the wall.

- Connect all the wires with wire connectors (A) by twisting matching wires as below
- Ground Wire (G, Green or Copper Wire) Green to Green or Copper to Green or Copper to Copper from junction box.
- Live Wire (L, Black) Black to Black Wire from junction box.
- Neutral Wire (N, White) White to White Wire from junction box.
- Once all connected, proceed to next step.

7. Install the canopy(E) on the mounting plate(C) with screws and decorative nut(F).

8. Install the light source and turn on the light, insert the glass rod(L) in the order of B# → A#positive → A#negative → C#.

Finish.

